



ASTRI Solar Fuels Preliminary Study to set LCOF Benchmark

ASTRI Annual Workshop, 2015

G. Nathan¹, P. Ashman¹, W. Saw¹, P. van Eyk¹, P. Guo¹, G. Metha¹, J. Alvino¹, C. Doonan¹, D. Losic¹, R. Karunakaran¹, A. Bayon², J. Hinkley², J. Pye³, W. Lipinski³, M. Venkataraman³, A. Weimer^{3,4}, T. Nann⁵, G. Andersson⁶, E. Stechel⁷, A. Steinfeld⁸

¹The University of Adelaide

²CSIRO

³Australian National University

⁴University of Colorado

⁵Flinders University

⁶University of South Australia

⁷Arizona State University

⁸ETH Zürich

11th February 2015

Need for Targets for cost and broad viability

- **IEA's Solar PACES Executive committee identified (at last meeting):**
 - Cost targets are needed to drive development of solar chemistry
 - None are available to our knowledge
- **Setting realistic targets is challenging because**
 - Solar chemistry is at a much earlier stage of development than solar power
 - No commercial plants have been built
 - No pilot-scale plants have been built of the full process
 - Significant differences between commercial and solar chemical process
 - Commercial processes are steady while the solar resource is intermittent
 - Commercial processes are 10 – 1,000 times larger
 - Significant differences between CST power and chemical process
 - Chemical plants operate at higher temperature than current power plants
 - Solar reactors typically differ from solar receivers
 - Solar chemistry are typically more complex, with more downstream processing
 - The diversity of chemical process is greater than for power plants
 - Many types of fuels and mineral processes
 - Many options within each type of chemical process
 - No standardised methodology with which to compare different options


Background

Conventional and Solar Gasification (and reforming)

Solar Gasification




Conventional Gasification



ASTRI Approach

- Selected Solar Fuels as the process closest to commercial
 - 1st Aust. Workshop on Solar Thermal Chemical Processes, Adel. Jan. 2013
 - Syngas production has been demonstrated at 250 kW
 - Long-term commercial drivers for fuels as high value product
- Developed a set of standard conditions by expert opinion
 - Solar Receiver Scale: 50 MW thermal
 - FT (mini) reactor scale: 1500 bbl/day (9.94m³/h)
- Selected Reference site as Geraldton, WA
 - good solar resource, 6.6 kWh/m²/day (DNI)
 - Ready access to all feedstocks (natural gas, coal, wood)
 - Access to seawater for growing algae (micro / macro)
- Selected common economic parameters

ASTRI Reference Location



Geraldton

Perth

- Oil-liquids pipeline
- Gas pipeline, existing
- - - Gas pipeline, proposed
- Ethane pipeline
-  Refinery
-  LPG plant
-  Gas and oil treatment plant
-  Gas treatment plant

**Australia
PETROLEUM
PIPELINE NETWORK**



ASTRI Reference Field Design



PARAMETER	CAVITY RECEIVER	EXTERNAL RECEIVER
Type of field	Sector	Surround
Design thermal incident power, MW_{th}	270.6	270.6
Tower height (100 MW_e), m	133	223
Solar multiple	1.33	1.33
Field size (100 MW_e), m^2	708,933	748,104
Optical efficiency of solar field [†]	56.4%	53.5%
Approximate field size, 50 MW_{th}	130,999	138,237


Field Design

Developed with SAM
 Scaled down from:
 $270 MW_{th} = 100 MW_e$

DESIGN POINT RADIATION TO RECEIVER	50,000	KW
Design point DNI	900	W/m^2
Annual energy yield	110.5	MWh
Solar field capacity factor (annual)	28.9%	
Solar field optical efficiency at design point	58.8%	


Turn-down of FT-reactor

- Current FT Reactors:
 - Employ large tubes
 - Take > 5 days to stabilise
 - No turn-down capability
- New mini-micro reactors
 - Employ small channels or tubes
 - ~ 10 × higher rates of heat transfer
 - Economic at much smaller scale (< 1/100)
 - Have potential for large turn-down
 - Being assessed within current ASTRI project
- Various approaches adopted in preliminary assessment
 - Three Hybrid processes: all achieve continuous production
 - Methane reforming: Storage 61% average daily output (requires turn-down)
 - Super-critical gasification: 6 hours storage (requires turn-down)



ASTRI Process modelling

Atmospheric pressure solar hybrid gasification system (SCTL)



- Processes models were developed for each technology option
 - All assumed “pseudo-steady-state” – steady at each time-step
 - Accounted for resource variability, but in different ways
 - Hybrid cases ensured full output was maintained throughout year

ASTRI – Key economic parameters

$$LCOF = \frac{\sum_{t=1}^n (I_t + M_t + F_t - S_t)/(1+r)^t}{\sum_{t=1}^n (E_t)/(1+r)^t}$$

LCOF = Levelised cost of fuel in \$/GJ (\$/Litre)

I_t = Investment expenditure or capital cost in the year t

M_t = Operations and maintenance cost in the year t

F_t = Feedstock cost in the year t

S_t = Annual sale price of any electricity in the year t , if produced from the process, in AUD

E_t = Quantity of energy produced (GJ), including electricity for sale in year t .

r = Discount rate

n = Amortisation period

ASTRI – Key economic parameters

SOLAR COST COMPONENTS	CURRENT COST (2014 AUD)	FUTURE COST 2020 (2014 AUD)	UNITS
Solar Field plus site costs	240	135	\$/m ²
Tower	51.0	46.6	\$/kW _{th}
Receiver (based on molten salt)	150.8	137.7	\$/kW _{th}
BOP solar	35.1	32.1	\$/kW _{th}
Solar field O&M	65	55.8	\$/((kW _{th} ·year)
Power generation	1025	965	\$/kW _e
Syngas storage	20,833	19,027	\$/GJ

ASTRI – Summary of economic analysis

Process	Technical feasibility (22%)	Solar share (10%)	Economic feasibility	-LCOF (\$/L)	Sustainability (20%)	-Feedstock sustainability (20%)	-CO ₂ emission (50%)	Stage of development (15%)	Overall	Priority
Solar mixed reforming of methane	7.8	3.0	6.8	\$1.0/L	2.5	1.0	4.0	6.5	5.7	1
Solar hybridized coal gasification via vortex flow reactor	6.3	3.0	5.3	\$1.2/L	1.0	1.0	1.0	4.5	4.3	2
Solar hybridized coal gasification via dual fluidised bed gasifier	7.5	3.0	7.1	\$0.9/L	1.0	1.0	1.0	6.0	5.4	1
Solar hybridized biomass gasification via dual fluidised bed gasifier	7.0	3.0	4.5	\$1.4/L	9.0	8.0	10.0	6.0	6.0	1
Supercritical water gasification of Algae	5.8	5.0	2.3	\$2.9/L	9.0	8.0	10.0	6.5	5.3	1
Thermochemical cycles	5.0	10.0	2.3	\$2.0/L	7.8	5.5	10.0	7.0	5.4	1

Final Comments

- ASTRI Milestones for costs by Dec 2016:
 - ❖ \$1.20/L for fossil fuel feedstock with a life-cycle emission of CO₂ that is at least 10% lower than conventional diesel, and
 - ❖ \$2.50/L for future renewable feedstock with a life-cycle emission of CO₂ that is at least 50% lower than conventional diesel.
 - Note: “Targets” could be set lower
- ASTRI milestone for wholistic viability:
 - ❖ develop a broad assessment system

Acknowledgements

ARENA



Australian Government

**Australian Renewable
Energy Agency**

The Australian Solar Thermal Research Initiative (ASTRI) Program is supported by the Australian Government through the Australian Renewable Energy Agency (ARENA).



Australian
National
University



THE UNIVERSITY
OF QUEENSLAND
AUSTRALIA



THE UNIVERSITY
of ADELAIDE



University of
South Australia



Flinders
UNIVERSITY

Thank you

